

Title: Machine for slitting plane packaging blanksTechnical Field

- 5 The invention relates to a machine for slitting plane packaging blanks, especially packaging blanks made of corrugated board, said machine including a driving roller assembly for advancing said packaging blanks, as well as at least one rotatable slitting roller with at least one knife for producing a front edge slit and/or a rear edge slit in each packaging blank.

10

Background Art

- A packaging machine of this type is known which includes a driving roller assembly and slitting knives, but this machine does not operate completely satisfactorily because it is rather complicated and operates in a rather unreliable manner. In addition,
15 this machine is rather expensive to manufacture.

Disclosure of Invention

- 20 The object of the invention is to provide a machine of the above type which even at a high working speed is more reliable than hitherto known, and which in addition is inexpensive to manufacture.

- The machine according to the invention is characterised in that the knife is circular,
25 i.e. sector-shaped, and defined by two knife edges, said knife extending across a central angle α of max. 300° , whereby said knife presents a gap between the edges, and that a portion of said knife adjacent the first knife edge is adapted to cut the front edge slit out of the front edge of said blank by means of the slitting roller and a driving motor connected to said slitting roller as well as by means of the controlling programme timer, whereas a second portion of the knife adjacent the other knife edge is
30 adapted to cut the rear edge slit out of a location on the blank adjacent the rear edge

- of said blank and rearwards through said rear edge by means of said slitting roller, said driving motor and said programme timer while said blank is advanced through the machine at a uniform speed. The resulting operational reliability is very high even at a high working speed, and the resulting slits present sharply cut edges. The machine is furthermore relatively inexpensive to manufacture. While each blank is advanced, the knife turns clockwise during the cutting procedure, but when the rear edge slit has been completed, said knife is turned counterclockwise until the first knife edge reaches its initial position and is ready to receive a subsequent blank.
- 10 According to the invention, the knife may be adapted to turn the knife edge out of an initial position by means of the slitting roller, the associated driving motor and the controlling programme timer in connection with the production of the front edge slit, in which position the knife edge is positioned at a predetermined central angle x (the arc $\frac{\pi}{180} \cdot rx$) from radius to the cutting site substantially corresponding to the desired
- 15 slit length, and a central angle x forwards until the front edge slit has been cut, whereafter said knife is retarded when the knife gap is positioned above the blank, and where the knife edge of said second knife portion or additional knife may be adapted also by means of said slitting roller, said driving motor and said programme timer to be turned from an initial angular position y and downwards into the blank at
- 20 the cutting site for the production of the rear edge slit and subsequently be turned a segment corresponding to the length of the rear edge slit of said blank, whereafter said second knife portion is retarded and then turned forwards in such a manner that the first knife edge reaches its initial position and is ready to receive a subsequent packaging blank. As a result, a very high operational reliability is obtained even at a
- 25 high working speed, and the slits present sharply cut edges. The machine is furthermore relatively inexpensive to manufacture.

During the cutting of both the front edge slit and the rear edge slit, the knife may according to the invention be adapted to run at a peripheral speed which is identical

30 with the advancing speed of the packaging blank by means of the slitting roller, the

driving motor and the programme timer. As a result a particularly high operational reliability is obtained.

Furthermore, according to the invention the knife may by means of the slitting roller,
5 the driving motor and the programme timer be adapted to ensure that during the re-
tarding movement the peripheral speed of said knife is finally zero. In this manner
the machine operates intermittently with the result that energy is saved during the
operation of said machine.

10 According to the invention the knife may extend across a central angle ν of max.
270°, especially 225°, and the angle x may be in the range $30^\circ < x < 70^\circ$, and the an-
gle y may be in the range $30^\circ < x < 70^\circ$, which corresponds to a knife gap of more
than 90°, especially 135°, said gap size turning out to be advantageous in practice.

15 Moreover, the driving motor may according to the invention be a servomotor, such
as an electric step motor or a mechanical/hydraulic driving motor, which turned out
to be particularly advantageous in practice.

When seen in the advancing direction of the packaging blanks, at least one sensor
20 device may according to the invention be mounted before the slitting rollers for de-
tecting the entering of said packaging blanks, said sensor device being adapted to ac-
tivate the programme timer on arrival of a packaging blank. As a result an increased
operational reliability is obtained.

25 According to the invention a back-pressure roller may be provided below the slitting
roller, said back-pressure roller for instance including two relatively thin circular
disks interspaced a distance corresponding to the thickness of the knife. The result-
ing edges cut in the front edge slit and the rear edge slit, respectively, are very sharp.

30 Finally, the back-pressure roller arranged below the slitting roller may according to
the invention be provided with a resilient coating, preferably a rubber coating,

whereby a particularly reliable operation is obtained.

Brief Description of the Drawings

5 The invention is explained in detail below with reference to the drawings, in which

Fig. 1 is a diagrammatic view of an embodiment of a portion of the machine according to the invention,

10 Fig. 2 is a perspective view of the embodiment of Fig. 1, where the first knife edge of the knife is in its initial position and is ready to cut a front edge slit in a packaging blank,

Fig. 3 corresponds to Fig. 2, but here the front edge slit of the blank has been cut and
15 the gap of the knife is positioned above said blank,

Fig. 4 corresponds to Fig. 3, but here the cutting of the rear edge slit of the blank has been completed, and

20 Fig. 5 is a perspective view of a blank provided with a front edge slit and a rear edge slit.

Best Mode for Carrying out the Invention

25 The machine shown in Fig. 1 is suited for slitting plane packaging blanks, especially packaging blanks made of corrugated board, but it can also be used for blanks made of cardboard. The machine includes a driving roller assembly 1 for advancing aligned packaging blanks 3 in the direction A through the machine. The driving roller assembly includes several sets of shafts 1'a, 1'b, 1''a and 1''b. Cylindrical friction members 5 are placed on these shafts and co-operate in pairs, such as 5' and 5''.
30 These friction members are preferably made of plastics or rubber.

In addition, the machine includes at least one rotatable slitting roller 7, which is provided with at least one knife 9 for cutting a front edge slit 11 or a rear edge slit 13 in the blank, cf. the blank 3 shown in Fig. 5.

5

The slitting knife 9 is circular and defined by two knife edges 9a and 9b. The first knife edge 9a is arranged at a first knife portion 9A, and the second knife edge 9b is arranged at a second knife portion 9B. The knife extends across a central angle v of max. 300° with the result that the knife presents a knife gap 19 between the knife
10 edges 9a and 9b of at least 60° .

The slitting roller 7 is connected to a driving motor 21 controlled by a programme timer 23, cf. Fig. 1. When a front edge slit 11 is to be produced in the blank 3 where the front edge 15 of the blank has reached the cutting site 25 of the knife, cf. Fig. 2,
15 this programme timer is adapted to turn the knife 9 in such a manner that the first knife edge 9a can be turned forwards from an initial position B in which position the knife edge 9a is positioned at a predetermined central angle x (the arc $\frac{\pi}{180} \cdot rx$, where r is the radius of the knife) from radius to the cutting site 25 substantially corresponding to the desired slit length f , cf. Fig. 5, and a central angle x forwards until
20 the front edge slit 11 has been cut, whereafter the programme timer 23 ensures that said knife is retarded when the knife gap 19 is positioned above the blank 3, cf. Fig. 3. During this procedure, the blank 3 is still forced forwards by the driving roller assembly 1'a, 1'b, 5', 5'', cf. Fig. 1, i.e. even when the knife does not engage the blank. In connection with the cutting of the rear edge slit 13 in the blank 3, cf. Fig. 5, the
25 programme timer 23 is adapted to turn the second knife edge 9b on the knife portion 9B or on an additional knife not shown out of an initial position y and downwards onto the cutting site 25 and subsequently to turn said knife edge a segment, cf. Fig. 4, corresponding to the length b of the rear edge slit 13 of the blank, cf. Fig. 5. Then the programme timer is adapted to retard the knife and subsequently turn said knife
30 forwards in such a manner that the first knife edge 9a reaches its initial position B,

cf. Fig. 2, in which the knife 9 is ready to receive a subsequent blank 3.

It is possible to provide the blank 3 with either a front edge slit 11 or a rear edge slit 13 or both slits in one and the same working operation while said blank 3 passes the
5 slitting knife 9. The front edge slit 11 is cut from the front edge 15 of the blank 3 and into said blank, whereas the cutting of the rear edge slit 17 is initiated at a distance from the rear edge of said blank and continued in a rearward direction through the rear edge 17.

10 During the cutting of both the front edge slit and the rear edge slit, the knife 9 is adapted to run at a peripheral speed which is identical with the advancing speed of the packaging blank 3 by means of the slitting roller, the driving motor and the programme timer. However, nothing prevents the peripheral speed from exceeding the advancing speed of the blank 3 at predetermined moments.

15 The slitting roller 7, the driving motor 21 and the programme timer 23 allow the knife 9 to be adapted to ensure that during the retarding movement the peripheral speed of said knife is finally zero.

20 The knife 9 can also extend across a central angle v of max. 270° , especially 225° , whereas the angle x can be in the range $30^\circ < x < 70^\circ$ and the angle y can be in the range $30^\circ < y < 70^\circ$.

The driving motor 21 can be a servomotor, such as an electric step motor or a me-
25 chanical/hydraulic driving motor. It is important that the driving motor can react sufficiently quickly to the command signals of the programme timer 23.

At least one sensor device 27 can be mounted before the slitting roller 7 when seen in the advancing direction A of the packaging blanks 3. This sensor device 27 is
30 adapted to detect the entering blanks 3, and it can for instance be an optical sensor and adapted to transmit an activating signal to the programme timer when a blank 3

passes by. In this manner the first knife edge 9a of the knife 9 can be caused to quickly enter its initial position B when said blank 3 reaches the knife 9.

As illustrated in the Figs. 1 to 4, a back-pressure roller 8 can be provided below the
5 slitting roller 7. This back-pressure roller 8 is for instance provided with two relatively thin, circular disks 8a, 8b interspaced a distance corresponding to the thickness of the knife. These circular disks are suited for making the edges of the front edge slit 11 and the rear edge slit 13 particularly sharp.

10 It should be noted that the knife 9 shown in the Figs. 2 to 4 is rather large and no knife edge is shown, but such a knife edge is, of course, provided in practice.

The back-pressure roller 8 arranged below the slitting roller 7 can be provided with a resilient coating, preferably made of rubber.

15

Furthermore it should be noted that the knife 9 rotates clockwise during the cutting of both the front edge slit and the rear edge slit, and that the direction of rotation is also clockwise from the moment the rear edge slit has been cut to the moment the first knife edge is in the initial position B. However, it is also possible to turn the
20 knife 9 during the latter procedure so as to rotate counterclockwise in order to cause the first knife edge to enter the initial position B.

The invention may be modified in many ways without thereby deviating from the scope of the invention.

Claims

1. A machine for slitting plane packaging blanks (3), especially packaging blanks made of corrugated board, said machine including a driving roller assembly
5 (1'a, 1'b, 5', 5'') for advancing said packaging blanks, as well as at least one rotatable slitting roller (7) with at least one knife (9) for producing a front edge slit (11) and/or a rear edge slit (13) in each packaging blank, **characterised in** that the knife (9) is circular, i.e. sector-shaped, and defined by two knife edges (9a, 9b), said knife extending across a central angle (ν) of max. 300° , whereby said knife presents a gap
10 (19) between the edges (9a, 9b), and that a portion (9A) of said knife (9) adjacent the first knife edge (9a) is adapted to cut the front edge slit (11) out of the front edge (15) of said blank (3) by means of the slitting roller (7) and a driving motor connected to said slitting roller as well as by means of the controlling programme timer, whereas a second portion (9B) of the knife (9) adjacent the other knife edge (9b) is
15 adapted to cut the rear edge slit (13) out of a location on the blank (3) adjacent the rear edge (17) of said blank and rearwards through said rear edge (13) by means of said slitting roller (7), said driving motor (21) and said programme timer (23) while said blank (3) is advanced through the machine at a uniform speed.
- 20 2. A machine according to claim 1, **characterised in**, that by means of the slitting roller (7), the driving motor (21) and the programme timer (23) the knife edge (9a) of the first knife portion (9A) is in connection with the production of the front edge slit (11) adapted to be turned from an initial position (B) in which the knife edge (9a) is positioned at a predetermined central angle x (the arc $\frac{\pi}{180} \cdot rx$) from radius to the cutting site (25) substantially corresponding to the desired slit length, and
25 a central angle x forwards until the front edge slit (11) has been cut, whereafter said knife (9) is retarded when the knife gap (19) is positioned above the blank (3), and that the knife edge (9b) of said second knife portion (9B) or an additional knife is adapted also by means of said slitting roller (7), said driving motor (21) and said
30 programme timer (23) to be turned from an initial angular position (y) and down-

wards into the cutting site (25) for the production of the rear edge slit (13) and subsequently be turned (9) a segment corresponding to the length (b) of the rear edge slit (13) of said blank, whereafter said second knife edge is retarded and then turned forwards in such a manner that the first knife edge (9a) reaches its initial position (B)
5 ready to receive a subsequent packaging blank (3).

3. A machine according to claim 1 or 2, **characterised in** that by means of the slitting roller (7), the driving motor (21) and the programme timer (23), the knife (9) is adapted during the cutting of both the front edge slit (11) and the rear edge slit
10 (13) to run at a peripheral speed which is substantially identical with the advancing speed of the packaging blank (3).

4. A machine according to claim 1, 2 or 3, **characterised in** that by means of the slitting roller (7), the driving motor (21) and the programme timer (23), the knife
15 (9) is adapted to ensure that during the retarding movement the peripheral speed of said knife (9) is finally zero.

5. A machine according to one or more of the claims 1 to 4, **characterised in** that the knife (9) extends across a central angle α of max. 270° , especially 225° , and
20 that the angle β is in the range $30^\circ < \beta < 70^\circ$, and the angle γ is in the range $30^\circ < \gamma < 70^\circ$.

6. A machine according to one or more of the claims 1 to 5, **characterised in** that the driving motor (21) is a servomotor, such as an electric step motor, or a me-
25 chanical/hydraulic driving motor.

7. A machine according to one or more of the claims 1 to 6, **characterised in** that at least one sensor device (27) is mounted before the slitting roller when seen in the advancing direction (A) of the packaging blanks (3), said sensor device (27) de-
30 tecting entering packaging blanks (3) and being adapted to activate the programme timer (23) on arrival of a packaging blank (3).

8. A machine according to one or more of the claims 1 to 7, **characterised in** that a back-pressure roller (30) is provided below the slitting roller (7), said back-pressure roller (30) for instance including two relatively thin, circular disks interspaced a distance corresponding to the thickness of the knife (9).

9. A machine according to one or more of the claims 1 to 8, **characterised in** that the back-pressure roller (30) arranged below the slitting roller is provided with a resilient coating preferably made of rubber.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/002133

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B26D3/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B26D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 00/02715 A (NEWELL GREGORY J) 20 January 2000 (2000-01-20) page 7, line 20 - line 30 page 8, line 8 - line 26 page 13, line 21 - line 28 page 14, line 21 - line 24 page 15, line 6 - line 31 page 16, line 11 - line 22 page 17, line 30 - line 31	1-9
Y	US 4 098 173 A (SCHAUMAN JAMES L) 4 July 1978 (1978-07-04) column 5, line 34 - line 40	1-9
Y	EP 1 120 209 A (ENGICO S R L) 1 August 2001 (2001-08-01) column 5, paragraph 42	7
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

G document member of the same patent family

Date of the actual completion of the international search

3 September 2004

Date of mailing of the international search report

10/09/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5918 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Vaglianti, G

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/002133

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 546 838 A (LONGWELL MICHAEL V) 20 August 1996 (1996-08-20) column 2, line 19 - line 28	9
Y	US 5 699 710 A (CREADEN DAVID E) 23 December 1997 (1997-12-23) column 8, line 47 - line 55	1
Y	GB 2 302 834 A (SCM CONTAINER MACH LTD) 5 February 1997 (1997-02-05) page 8, paragraph 2; figures	1

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/002133

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0002715	A	20-01-2000	WO 0002715 A1	20-01-2000
US 4098173	A	04-07-1978	NONE	
EP 1120209	A	01-08-2001	IT MI20000083 A1	24-07-2001
			EP 1120209 A2	01-08-2001
			US 2001009121 A1	26-07-2001
US 5546838	A	20-08-1996	NONE	
US 5699710	A	23-12-1997	AU 701450 B2	28-01-1999
			AU 6290196 A	05-03-1997
			BR 9610105 A	23-02-1999
			EP 0843614 A1	27-05-1998
			JP 11510442 T	14-09-1999
			WO 9705992 A1	20-02-1997
GB 2302834	A	05-02-1997	EP 0752299 A1	08-01-1997